DECLARATION OF PERFORMANCE

No. SSC 0003

1. Unique identification code of the product type

Dry-Pressed ceramic tiles

2. Type, batch or serial number or any other element allowing identification of the construction product

| No. | Туре | Group |
|-----|----------------------|-------|
| 1 | Gres Porcelain Tiles | Blb |
| 2 | Floor Tiles | Blb |
| 3 | Floor Tiles | Blla |
| 4 | Floor Tiles | BIIb |
| 5 | Wall Tiles | BIII |

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer

For internal and external walls & floors

4. Name, registered trade name or registered trade mark and contact address of the manufacturer

SOSUCO Ceramic Company Limited

Plant: 33/2 Moo 2, Rim-Klong Rapeepat Road, Nongpling, Nongkhae, Saraburi 18140 Thailand

5. Where applicable, name and contact address of the authorized representative

N/A

- 6. System or systems of assessment and verification of constancy of performance of the construction product

 System 4
- 7. In case of the declaration if performance concerning, a construction product covered by a harmonized standard

EN 14411

8. Declared performances

| Essential Characteristics | Performance | Harmonised technical specification & method | | |
|--|-------------------------------------|---|--|--|
| Reaction to fire (Only tiles intended for use subjected to reaction to fire regulations) | A1 Classified without testing (CWT) | Decision 96/603/EC,as amended | | |
| Water Absorption for: | | 70 | | |
| - Blb | 0.5% < E ≤ 3% | | | |
| - Blla | 3% < E ≤ 6% | EN ISO 10545-3 | | |
| - BIIb | 6% < E ≤ 10% | | | |
| - BIII | E > 10% | 9.7 | | |
| Breaking Strength for: | (Thickness < 7.5 , ≥ 7.5 mm) | | | |
| - Blb | (≥ 700, ≥ 1100 N) | 100 | | |
| - Blla | (≥600, ≥ 1000 N) | EN ISO 10545-4 | | |
| - BIIb | (≥ 500 , ≥ 800 N) | 122 | | |
| - BIII | (≥ 200 , ≥ 600 N) | | | |
| Thermal Shock Resistance (where relevant according to material) | NPD | EN ISO 10545-9 | | |
| Durability , freeze / thaw / frost resistance (for Bla) | NPD | EN ISO 10545-12 | | |
| Release of dangerous substance - Lead | NPD | EN ISO 10545-15 | | |
| - Cadmium | NPD | | | |

^{9.} The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Technology Division Manager
Sosuco Ceramic Company Limited

12 /09 / 2022